

# Nylon TWINWHEEL™ Casters



RWM TwinWheel™ casters come in a variety of sizes with many stem options and small top plates. The wheels work independently, enabling easy swivel action. These casters are great for medical equipment, audio-visual carts, institutional equipment, bath lifts, nurseries, seating, store fixtures, electronic equipment, institutional furniture and equipment, home and office furniture and other light duty institutional applications.



**Nylon TwinWheel™ with Grip Neck Wood Stem**

MODEL TW-NY-40MM-S-SC



**Nylon TwinWheel™ with Soft Polyurethane Tread with Brake**

MODEL TW-PU-100MM-S-SC-THD-WB



**Nylon TwinWheel™ with Grip Ring Stem**

MODEL TW-NY-100MM-S-SC



**Nylon TwinWheel™ with Top Plate**

MODEL TW-NY-40MM-S



**Nylon TwinWheel™ with Top Plate and Brake**

MODEL TW-NY-50MM-S-WB

**A variety of stems and mounting plates not listed are also available.**

## SPECIFICATIONS

TWINWHEEL™ Part Number	Wheel Diameter	Wheel Type	Capacity lbs.	Stem/Plate	Stem/Plate Dimension	Overall Height	Swivel Radius
TW-NY-40MM-S	1-1/2" (40mm)	Nylon	50	Plate	1-1/2" Square Top Plate with 1" Spacing	2-3/16"	1-9/16"
TW-NY-40MM-S-SC				Stem	1-19/32" Grip Neck Wood Stem	2-1/16"	1-9/16"
TW-NY-40MM-S-SC-WB				Stem	1-19/32" Grip Neck Wood Stem with Wheel Brake	2-1/16"	1-15/16"
TW-NY-40MM-S-WB				Plate	1-1/2" Square Top Plate with 1" Spacing with Wheel Brake	2-3/16"	1-15/16"
TW-NY-50MM-S	2" (50mm)	Nylon	66	Plate	1-1/2" Square Top Plate with 1" Spacing	2-3/16"	2"
TW-NY-50MM-S-SC				Stem	1-19/32" Grip Neck Wood Stem	2-3/8"	2"
TW-NY-50MM-S-WB				Plate	1-1/2" Square Top Plate with 1" Spacing with Wheel Brake	2-9/16"	2-3/8"
TW-NY-50MM-S-SC-WB				Stem	1-19/32" Grip Neck Wood Stem with Wheel Brake	2-3/8"	2-3/8"
TW-NY-100MM-S-SC	4" (100mm)	Nylon	220	Stem	7/16" x 1" Grip Ring Stem	4-1/4"	3-1/2"
TW-NY-100MM-S-SC-THD				Stem	1/2" - 13" x 1" Threaded Stem	4-1/4"	3-1/2"
TW-NY-100MM-S-SC-THD-WB				Stem	1/2" - 13" x 1" Threaded Stem with Wheel Brake	4-1/4"	4-1/2"
TW-NY-100MM-S-SC-WB				Stem	7/16" x 1" Grip Ring Stem with Wheel Brake	4-1/4"	4-1/2"
TW-PU-100MM-S-SC	4" (100mm)	Polyurethane	220	Stem	7/16" x 1" Grip Ring Stem	4-7/16"	3-1/2"
TW-PU-100MM-S-SC-THD				Stem	1/2" - 13" x 1" Threaded Stem	4-1/2"	3-1/2"
TW-PU-100MM-S-SC-THD-WB				Stem	1/2" - 13" x 1" Threaded Stem with Wheel Brake	4-1/2"	4-1/2"
TW-PU-100MM-S-SC-WB				Stem	7/16" x 1" Grip Ring Stem with Brake	4-7/16"	4-1/2"
TW-NY-125MM-S-SC-WB	5" (125mm)	Nylon	220	Stem	7/16" x 1-1/4" Grip Ring Stem with Wheel Brake	5-1/2"	4-3/4"
TW-NY-125MM-S-SC-WB	5" (125mm)	Nylon	250	Stem	7/16" x 1-1/2" Grip Ring Stem with Wheel Brake	5-1/2"	4-3/4"
TW-NY-125MM-S-SC-THD-WB				Stem	1/2" - 13" x 1" Threaded with Brake	5-7/16"	4-3/4"
TW-NY-125MM-S-SC-THD				Stem	1/2" - 13" x 1" Threaded	5-7/16"	4-3/4"

UP TO 250 POUND CAPACITY