

# S75 Stainless Steel Casters

RAPIDSTOCK

RWM's S75 Stainless Steel Casters are ideally suited for frequent washdown applications. This caster can handle cleaning agents, steam, caustic solutions or other corrosive agents that can cause rust or corrosion.



S75-GTB-0625-S-SSBB-WTHB

## Features

**Raceway Design:** Patented Kingpinless™ single ball bearing precision machined raceway. 3" diameter raceway with 1/2" stainless ball bearings

**Leg Thickness:** 1/4"

**Mounting Plate Size:** 4-1/2" x 6-1/2" x 1/4"

**Bolt Hole Spacing:** 2-7/16" x 4-15/16" slotted to 3-3/8" x 5-1/4"

**Mounting Bolt Diameter:** 1/2"

View  
CAD Models  
On Our  
Website!

## Applications

RWM's Stainless Steel Casters feature surgical grade 304 stainless steel that is highly resistant to conditions that would normally corrode and rust regular zinc plated steel casters. Our Stainless Steel Casters are ideal for wet or damp conditions and harsh environments that may rust or corrode standard zinc casters. These casters are well suited for rugged duty and are designed for wash-down applications such as food processing plants, food service equipment, large volume high temperature bakery and food cooking facilities, bakery and bread racks, slaughter houses, fisheries, seafood processing plants, stock and maintenance carts, ingredient bins, institutional service carts and equipment, hatcheries, pharmaceutical plants and laboratories.

## Options


- SCWB** Stainless Steel Cam Wheel Brake
- SL** Swivel Lock
- SR** Sealed Swivel Raceway
- SSBB** Stainless Steel Ball Bearing
- SSRB** Stainless Steel Roller Bearing
- WTHB** Welded "T" Handle Brake

## CUSTOM FABRICATION

If you don't find the right caster for your application, let our engineering team create one for you.

We custom design caster, wheel and non-powered material handling solutions to meet your individual needs.

Many of our new product innovations offer major improvements in performance and maximize value to our customers.



UP TO 2,500 POUND CAPACITY

SPECIFICATIONS									
Wheel Diameter	Wheel Width	Wheel Type	Capacity lbs.	Overall Height	Swivel Caster Model Number			Swivel Lead	Approx. Weight lbs.
					Straight Roller Bearing	Ball Bearing	Tapered Roller Bearing		
6"	2-1/2"	Durastan	1600	7-1/2"	S75-DUR-0625-S			1-3/8"	11.5
		GT	2300			S75-GTB-0625-S			11.5
		Urethane on Iron	1620		S75-UIR-0625-S		S75-UIT-0625-S		16.5
6"	3"	Durastan	2000	7-1/2"	S75-DUR-0630-S			1-3/8"	12.5
		Solid Urethane	2000		S75-MUR-0630-S	S75-MUB-0630-S			12.5
		Urethane on Iron	2000		S75-UIR-0630-S		S75-UIT-0630-S		17.5
8"	2-1/2"	Durastan	2000	10-1/8"	S75-DUR-0825-S			2-1/16"	15.0
		GT	2400			S75-GTB-0825-S			15.0
		Urethane on Iron	2000		S75-UIR-0825-S		S75-UIT-0825-S		18.5
8"	3"	Durastan	2500	10-1/8"	S75-DUR-0830-S			2-1/16"	16.5
		Omega	1600		S75-UOR-0830-S		S75-UOT-0830-S		19.0
		Solid Urethane	2500		S75-MUR-0830-S	S75-MUB-0830-S			16.5
		Urethane on Iron	2500		S75-UIR-0830-S		S75-UIT-0830-S		19.5
10"	2-1/2"	Durastan	2500	11-1/2"	S75-DUR-1025-S			2-1/4"	16.5
		Urethane on Iron	2370		S75-UIR-1025-S		S75-UIT-1025-S		21.5
10"	3"	Durastan	2500	11-1/2"	S75-DUR-1030-S			2-1/4"	20.0
		GT	2500			S75-GTB-1030-S			20.0
		Omega	2000		S75-UOR-1030-S	S75-UOB-1030-S	S75-UOT-1030-S		22.0
		Rubber on Aluminum-EHT	2000			S75-RAB-1030-S	S75-RAT-1030-S		20.3
		Solid Urethane	2500		S75-MUR-1030-S	S75-MUB-1030-S			20.0
		Urethane on Iron	2500		S75-UIR-1030-S		S75-UIT-1030-S		22.5
		Ultra Thick Urethane	2500		S75-UTR-1030-S		S75-UTT-1030-S		25.0
12	2-1/2"	Durastan	2500	13-1/2"	S75-DUR-1225-S			2-11/16"	20.5
		Urethane on Iron	2500		S75-UIR-1225-S		S75-UIT-1225-S		23.5
12	3"	Durastan	2500	13-1/2"	S75-DUR-1230-S			2-11/16"	22.5
		Rubber on Aluminum-EHT	2280			S75-RAB-1230-S	S75-RAT-1230-S		24.5
		Urethane on Iron	2500		S75-UIR-1230-S		S75-UIT-1230-S		26.5
		Ultra Thick Urethane	2500		S75-UTR-1230-S		S75-UTT-1230-S		28.0

To order a rigid caster, change the "S" to "R" in the model number. For example: "S75-DUR-0830-R". To order a rig only, omit the blue letters. For example: "S75-0830-S". Dimensions shown are nominal. If precise dimensions are required, consult your RWM representative. For approximate weight of our rigid caster, deduct 5.4 pounds.

UP TO 2,500 POUND CAPACITY