

The RWM Signature™ Premium Wheel has a lightweight, reinforced nylon core with a high strength non-marking elastomeric rubber tread. The round tread provides easy rolling. Our durable nylon core is six times stronger than polypropylene. The performance rubber tread is cut, tear and corrosion resistant and will not chunk out. It has the highest strength-to-weight ratio than any other wheel in the industry. The Signature™ Premium Wheel is excellent for floor protection, continuous towing and noise reduction.

Applications

The RWM Signature™ Premium Wheel is ideal for:

- ◆ platform trucks
- ◆ material handling carts
- ◆ warehouse & factory applications
- ◆ food service
- ◆ drywall carts
- ◆ assembly line dollies



SWB-0820-08

Features

Wheel Bearing: Choice of straight roller or precision ball bearing
Temperature Range: -40° to 200°F
Hardness: 70 Shore A
Bores: 1.190"

The RWM Signature™ Premium Wheel has a light-weight, reinforced offset nylon core with a high strength non-marking elastomeric rubber tread. The round tread provides easy rolling. Our durable nylon core is six times stronger than polypropylene. The performance rubber tread is cut, tear and corrosion resistant and will not chunk out. It has the highest strength-to-weight ratio than any other wheel in the industry and provides excellent floor protection and noise reduction.

Applications

The RWM Hand Truck Signature™ Premium Wheel is ideal for:

- ◆ two wheelers
- ◆ convertibles
- ◆ all material handling carts











SW2








Features

Wheel Bearing: Precision flanged ball bearing
Temperature Range: -40° to 200°F
Hardness: 70 Shore A

UP TO 800 POUND CAPACITY

SPECIFICATIONS							
 Wheel Diameter	 Wheel Width	 lbs. Capacity	 Axle Diameter	 Straight Roller Bearing	 Sealed Precision Ball Bearing	 Hub Length	 Approx Weight
4"	2"	400	1/2"	SWR-0420-08	SWB-0420-08	2-7/16"	1.3
5"	2"	500	1/2"	SWR-0520-08	SWB-0520-08	2-7/16"	1.5
6"	2"	600	1/2"	SWR-0620-08	SWB-0620-08	2-7/16"	2.0
8"	2"	700	1/2"	SWR-0820-08	SWB-0820-08	2-7/16"	2.8

The SW1 and SW2 wheels are for hand trucks only.

SPECIFICATIONS						
 Wheel Diameter	 Wheel Width	 Capacity	 Axle Diameter	 Sealed Precision Ball Bearing	 Hub Length	 Approx Weight
8"	2"	600*	5/8"	SW1	2"	2.30
10"	2"	800*	5/8"	SW2	2.5"	3.00

*Wheel capacity ratings do not reflect hand truck ratings.



UP TO 800 POUND CAPACITY